

iCombi® Pro.

Modellenoverzicht

Te bestellen van vanaf 6 mei 2020



| iCombi Pro | XS 6-2/3 | 6-1/1 | 10-1/1 | 6-2/1 | 10-2/1 | 20-1/1 | 20-2/1 |
|-----------------------------------|-----------------------|----------------------------|----------------------------|-------------------------|-----------------------|----------------------------|-------------------------|
| Capaciteit | 6 × 2/3 GN | 6 × 1/1 GN | 10 × 1/1 GN | 6 × 2/1 GN | 10 × 2/1 GN | 20 × 1/1 GN | 20 × 2/1 GN |
| Aantal maaltijden per dag | 20–80 | 30–100 | 80–150 | 60–160 | 150–300 | 150–300 | 300–500 |
| Lading in de lengte (GN) | 1/2, 2/3, 1/3, 2/8 GN | 1/1, 1/2, 2/3, 1/3, 2/8 GN | 1/1, 1/2, 2/3, 1/3, 2/8 GN | 2/1, 1/1 GN | 2/1, 1/1 GN | 1/1, 1/2, 2/3, 1/3, 2/8 GN | 2/1, 1/1 GN |
| Breedte | 655 mm | 850 mm | 850 mm | 1072 mm | 1072 mm | 877 mm | 1082 mm |
| Diepte | 621 mm | 842 mm | 842 mm | 1042 mm | 1042 mm | 913 mm | 1117 mm |
| Hoogte | 567 mm | 754 mm | 1014 mm | 754 mm | 1014 mm | 1807 mm | 1807 mm |
| Aansluiting water | R 3/4" | R 3/4" | R 3/4" | R 3/4" | R 3/4" | R 3/4" | R 3/4" |
| Afvoer water | DN 40 | DN 50 | DN 50 | DN 50 | DN 50 | DN 50 | DN 50 |
| Waterdruk | 1,0 - 6,0 bar | 1,0 - 6,0 bar | 1,0 - 6,0 bar | 1,0 - 6,0 bar | 1,0 - 6,0 bar | 1,0 - 6,0 bar | 1,0 - 6,0 bar |
| Elektrisch | | | | | | | |
| Gewicht | 67 kg | 99 kg | 127 kg | 137 kg | 179 kg | 263 kg | 336 kg |
| Aansluitwaarde | 5.7 kW | 10.8 kW | 18.9 kW | 22.4 kW | 37.4 kW | 37.2 kW | 67.9 kW |
| Zekering | 3 × 10 A | 3 × 16 A | 3 × 32 A | 3 × 35 A | 3 × 63 A | 3 × 63 A | 3 × 100 A |
| Aansluiting | 3 NAC 400 V | 3 NAC 400 V | 3 NAC 400 V | 3 NAC 400 V | 3 NAC 400 V | 3 NAC 400 V | 3 NAC 400 V |
| Output convectie modus | 5.4 kW | 10.25 kW | 18 kW | 21.6 kW | 36 kW | 36 kW | 66 kW |
| Output stoom modus | 5.4 kW | 9 kW | 18 kW | 18 kW | 36 kW | 36 kW | 54 kW |
| Gas | | | | | | | |
| Gewicht | | 117 kg | 155 kg | 144 kg | 192 kg | 284 kg | 379 kg |
| Aansluitwaarde elektrisch systeem | | 0.6 kW | 0.9 kW | 0.9 kW | 1.5 kW | 1.3 kW | 2.2 kW |
| Zekering | | 1 × 16 A | 1 × 16 A | 1 × 16 A | 1 × 16 A | 1 × 16 A | 1 × 16 A |
| Aansluiting | | 1 NAC 230 V | 1 NAC 230 V | 1 NAC 230 V | 1 NAC 230 V | 1 NAC 230 V | 1 NAC 230 V |
| Gas aansluiting | | 3/4" IG | 3/4" IG | 3/4" IG | 3/4" IG | 3/4" IG | 3/4" IG |
| Gas /LPG G31/LPG G30* | | | | | | | |
| Max. nominaal thermische waarde | | 13 kW/13 kW/ 13.5 kW | 22 kW/22 kW/ 23 kW | 28 kW/28 kW/ 29.5 kW | 40 kW/40 kW/ 42 kW | 42 kW/42 kW/ 44 kW | 80 kW/80 kW/ 84 kW |
| Output convectie modus | | 13 kW/13 kW/ 13.5 kW | 22 kW/22 kW/ 23 kW | 28 kW/28 kW/ 29.5 kW | 40 kW/40 kW/ 42 kW | 42 kW/42 kW/ 44 kW | 80 kW/80 kW/ 84 kW |
| Output stoom modus | | 12 kW/12 kW/ 12.5 kW | 20 kW/20 kW/ 21 kW | 21 kW/21 kW/ 22 kW | 40 kW/40 kW/ 42 kW | 38 kW/38 kW/ 40 kW | 51 kW/51 kW/ 53.5 kW |

* To guarantee proper operation, the appropriate connection flow pressure must be ensured:
Natural gas H G20 18 25 mbar (0.261 0.363 psi), Natural gas L G25: 20 30 mbar (0.290 0.435 psi), LPG G30 und G31: 25 57,5 mbar (0.363 0.834 psi).

RATIONAL Nederland
Grootkeukentechniek BV
Twentepoort West 7
7609 RD Almelo

0546 - 546 000
info@rational.nl
www.rational.nl

